

caroma®

CI/SfB	(74.1)	g3
Date	May 2011	

Supersedes all previous issues

Somerton Smart 270 Easy Height Elongated

2.7.2

**1.28/0.8 gpf (4.8/3 lpf) Water Saving Dual Flush High Efficiency Toilet (HET)
Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet**



HIGH EFFICIENCY TOILET
HET

c-UPC®
IAPMO listed for USA & Canada

Somerton Smart 270 Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) Dual Flush HET

Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



A modern concept close coupled **1.28/0.8 gpf (4.8/3 lpf) Somerton Smart 270 Easy Height Elongated** dual flush washdown toilet installation designed to provide a seat height of between 17" to 19" (430 to 485mm) measured to the top of the toilet seat. The closet bowl has been designed with rough-in of **10" (255mm) to 12" (305mm)** provided by plastic offset outlet connector option. The tank incorporates the high performance outlet valve which has been specially developed with the 270 Easy Height Elongated bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 lpf) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important. **Important:** The Somerton Smart 270 Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Closet bowl:** **Somerton Smart 270 Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush washdown closet bowl with box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.
- Tank:** **Somerton Tank** – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas. Code No. 750109. Pan weight 68 lbs (31 kg) Tank weight 24 lbs (11 kg).
- Weight:** **Standard Bottom Entry Tank** – available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.
- Water Control Valve:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Fixing:** The following Caroma seats are recommended: **Detachable** Code No. 301032, **Easy Closing** Code No. 326222, **Standard** Code No. 326707, White only.
- Seats:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.
- Color:** White only.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

